

165 KRX2

2-way K2 Power kit

- K2 composite sandwich cone

Impact and details

- Zamak chassis

Rigid and non-magnetic

- Aluminum phase plug

Better midrange directivity

- Butyl surround

Excellent reliability

- Serial number engraved in the block

Authenticity certificate

- 2 Ohm voice coil

Sensitivity rise

- Inverted dome tweeter TN53K

Smoothness and accuracy

- Neodymium ring magnet

Very high linearity and dynamics

- Foam separate surround

Extended frequency response

- Phase part

Slight directivity

- Adjustable tweeter level per step of 3dB

Installation flexibility

- Polypropylene capacitor

Natural treble reproduction

- Air core inductor

Resistant to parasites, maximum dynamics

- Super Tweeter

Emphasizes the extreme treble



Technical characteristics :

Woofer: 6 1/2" (165mm)

Voice coil: 1 9/16" (40mm)

Magnet: 3 15/16" (100mm)

TN53K tweeter

Inverted dome

Separate crossover: Full/12 12/18dB/oct (4.7kHz)

Adjustable tweeter level: (0, -3, -6dB)

Max. power: 200W

Nom. power: 100W

Sensitivity (2.83V/1m): 93dB

Frequency response: 70Hz – 20kHz

Accessories: grilles supplied

It makes the difference:

- 2 Ohm voice coil
- High sensitivity
- Tweeter sound level adjustment

