

ACCESS 165 AS3

3 way component kit

- (DFS®) Dual Fiberglass Structure cone
High resistance (Power, climatic conditions, humidity...)
- Grilles new design
Profiled

- Butyl surround
Longlife

- Adjustable tweeter level
(3 positions : -3 / 0 / +3dBoct)
Soundstage positioning
- Air core inductors
Insensitive to parasite interferences



- ABS basket with 20% of fiberglass
Non magnetic, non resonant
- 25mm (1") voice coil (2 Kapton® layer)
High power handling

- 85mm magnet
High sensitivity

- 80mm (3") midrange
Compact, easy to install

- Aluminum inverted dome tweeter
Accurate treble

WHAT MAKES THE DIFFERENCE

- Cone DFS® (Dual fiberglass Structure),
[climatic and power] high resistance
- High sensitivity (Direct headunit using)
- Compact midrange 3¹/₈ (80mm) (easy to install)
- Tweeter level adjustment - Extended in low frequencies
- Power handling

TECHNICAL CHARACTERISTICS

Woofer diameter: 6¹/₂" (165mm)

Midrange diameter: 3" (80mm)

Voice-coil diameter: 1" (25mm)

Voice-coil height: 0⁹/₁₆" (15mm)

Magnet: 3¹/₈" (85mm)

Tweeter: Aluminum inverted dome

Separate crossover: 12dB/Oct

Adjustable Tweeter level: 3 positions [-3/0/+3dB]

Max. power: 160W

Nom. power: 80W

Sensitivity (2.83V/1m): 90dB

Frequency response: 55Hz - 20kHz

Accessories: Supplied grilles

 **Performance**
CREATE YOUR SOUND

 **FOCAL**
THE SPIRIT OF SOUND