

DIRECT FET® AMPLIFIER FD 4.350

Ultra-compact 4-channel amplifier

• Aluminium chassis
high heat dissipation

• Compatible with OEM head units thanks to the
audio transformers - auto detection feature



• Hidden connectors
Stackable chassis
Built-in active crossovers

• D Class amplification
Optimal integration of Direct FET® Technology

KEY POINTS

- D Class – Direct Fet® Technology - Efficient heat dissipation and precision
- Stable under 2 Ohms
- Stackable aluminium chassis with high heat dissipation
- Low noise operational amplifier New Japan Radio® NJM4580
- Low ESR capacitors - 105°C (220°F)
- Pseudo-balanced inputs
- Cable accessories included - easy to install



TECHNICAL SPECIFICATIONS



4/3/2-channel D Class amplifier

High-level inputs with auto-detect / RCA
low-level inputs

CEA power (4 Ohms): 4x58 Watts RMS

Power max (2 Ohms): 4x100 Watts RMS

Power max (4 Ohms bridged): 2x200 Watts RMS

Configurable high-pass/low-pass crossover: 40Hz-400Hz

Full range mode

Protections: Short circuit / low impedance / reversal of
polarity / DC / power drop / heat protection

Dimensions (L x H x W):

7¹³/₁₆ x 4¹/₄ x 1¹¹/₁₆ [199x108x43mm]

Weight: 1.8 lbs

Performance
CREATE YOUR SOUND

FOCAL
THE SPIRIT OF SOUND