

K2 POWER E 25 KX

10" Subwoofer



Rubber surround with catenary profile

- Reliability and robustness
- high excursion

Aluminum chassis new design

- Rigid, antimagnetic with exclusive design for a better excursion

K2 Power sandwich cone

- Dynamic & precise

Progressive spider profile

- Stress area distributed

Exclusive VC venting system

- High SPL and high power handling

Push button terminal

- Simplified wiring

Motor "dual magnet" 4 Ω

- Linearity and high power



WHAT MAKES THE DIFFERENCE

- Compact size
- High power
- For sealed and vented enclosure (0.6 to 0.77 cu ft (17 to 22L) in sealed for optimized performance

TECHNICAL CHARACTERISTICS

Subwoofer

Diameter: 10" (250mm)
Voice coil diameter: 2^{9/16}" (65mm)
Voice coil height: 2^{3/16}" (55mm)
Motor: Magnet

Tweeter: Composite K2 Power "W" sandwich cone
Max.power: 1200W
Nom.power: 600W RMS

Sensitivity (2,83V/1m): 84.5dB
Frequency response: 25Hz - 500Hz
Impedance: dual 2x4 Ω



Elite

"HAUTE COUTURE" SOUND



FOCAL®

THE SPIRIT OF SOUND