

K2 POWER E 30 KX

12" Subwoofer



Rubber surround with catenary profile

- Reliability and robustness
- high excursion

K2 Power sandwich cone

- Dynamic & precise

Aluminum chassis new design

- Rigid, antimagnetic with exclusive design for a better excursion

Progressive spider profile

- Stress area distributed

Exclusive VC venting system

- High SPL and high power handling

Push button terminal

- Simplified wiring

Motor "dual magnet" 4 Ω

- Linearity and high power



WHAT MAKES THE DIFFERENCE

- Impressive power handling
- High SPL
- High excursion
- For sealed and vented enclosure
(1 to 1,3 cu ft [28 to 35l] in sealed for optimized performance)

TECHNICAL CHARACTERISTICS

Subwoofer

Diameter: 12" (300mm)
Voice coil diameter: 2^{9/16}" (65mm)
Voice coil height: 2^{3/16}" (55mm)

Motor: Magnet

Tweeter: Composite K2 Power "W" sandwich cone
Max. power: 1600W

Nom. power: 800W RMS

Sensitivity (2,83V/1m): 86.5dB
Frequency response: 20Hz - 500Hz
Impedance: dual 2x4 Ω



Elite

"HAUTE COUTURE" SOUND



FOCAL®

THE SPIRIT OF SOUND