FDP 1.900

Full Range Class D Mono amplifier

- High-pass, low-pass, and band-pass crossover
- 40Hz EQ adjustable 0 to 6dB
- Continuous Phase adjustment 0-180°
- Small size Easy integration in a vehicle

FOCAL

-

• Compact Aluminum chassis High thermal dissipation

- High and low-level inputs Suits any installation
- "Auto Power On" with high-level input Easier Integration with factory head unit
- Selectable Balanced or Unbalanced inputs
- \bullet Two amplifiers can be bridged, 1800 W 4Ω
- For higher power applications

 Designed & Engineered in California
- Not a "me too" amplifier design

TECHNICAL CHARACTERISTICS

Power into 4 0hms: 1x550W rms Power into 2 0hms: 1x900W rms Signal/noise ratio: >95dB (A) Bass Boost: 0 to +6dB @ 40Hz Frequency response (-1dB): 5Hz-25kHz Continuous phase Adjustment: 0-180°

Adjustable gain 200mV to 10V Dimensions (HxLxD): 2 x 10 x 7 ^{3/4} in (50x254x196mm) Protections: Short-circuit, thermal overload, polarity reversal, DC

ADVANTAGES

• Very small size for power output

High-level input, compatible with 0EM Stereo

• Can be used in full range

• Easily accessible settings

Invisible mounting bracket

Highest level of crossover flexibility

• Remote sub control





• 4G Power & Ground Terminals

FOCA

• Remote sub control with LED clipping indicator